

Sl No	Description of item	Unit	No	L	B	D	Qty	Rate	Amount
			100.00				100.00		
						Mtrs	100.00	10.75	1075.00
51	Wiring for lighting/power circuit using one of FRLS PVC insulated 1100V grade, multi-strand Copper conductor single core wire in open or concealed system of wiring as per IS-694:1990 & confirming to GTP of GROUP -B. 1.5 sqmm SR No:3/2.6.2	Mtrs							
			600.00				600.00		
						Mtrs	600.00	15.90	9540.00
52	Wiring for lighting/power circuit using one of FRLS PVC insulated 1100V grade, multi-strand Copper conductor single core wire in open or concealed system of wiring as per IS-694:1990 & confirming to GTP of GROUP -B. 2.5 sqmm SR No:3/2.6.3	Mtrs							
			300.00				300.00		
						Mtrs	300.00	24.90	7470.00
53	Wiring for lighting/power circuit using one of FRLS PVC insulated 1100V grade, multi-strand Copper conductor single core wire in open or concealed system of wiring as per IS-694:1990 & confirming to GTP of GROUP -B.4 sqmm SR No:3/2.6.4	Mtrs							
			200.00				200.00		
						Mtrs	200.00	36.30	7260.00
54	Supplying heavy gauge PVC conduit pipe dia mm thick conforming to IS 2509 with suitable size bends, junction boxes, adhesive paste etc., and fixing using inverted wood plugs in case of RCC ceiling and RCC wall / stone structure or rawl plugs in case of brick walls and cement plastering the damaged portion using heavy gauge saddles at an interval of 700mm using NF	Mtrs							
			300.00				300.00		
						Mtrs	300.00	54.00	16200.00
55	Supplying and fixing of class A (medium duty) GI pipe of wall thickness not less than 3.25mm on pole/wall/drain crossing with necessary clamping arrangements for UG cable of 1.1 KV 40mm SR No:6/2/7.1	Mtrs							
			30.00				30.00		
						Mtrs	30.00	345.00	10350.00
56	Supply and Installation / Fixing / Provision of Pole box with HRC Fuse / MCB provision and suitable connector / terminal for 3 Ph / 1 Ph connections with Loop-In & Loop-Out terminals for 10 Sqmm / 25 Sqmm 3.5 C Al/Ar / Cu/Ar Cable and branch out 2.5 Sqmm 2 core Al/Cu PVC Insulated cable, enclosed in a Thermoplastic, Polystyrene enclosure, which should be shock proof, safe, IP65(Weather Proof), rust proof, dust proof, water proof having Internally Embedded Gasket with provision for cable entry through IP65 Thermoplastic, polyamide glands and/or grommets.200mmx200mmx98mm SR No:58/6.41.1	Mtrs							
			75.00				75.00		
						Mtrs	75.00	2178.00	163350.00
57	P&S Submersible Single Phase Pumpset	Nos							
	Providing and Supplying Submersible single Phase 2.0 HP /1.5 KW 30 Stage Capacity Company for ATALANTA / SUGUNA / CRI / KIRLOSKAR / OTHER EQUIVALENT PUMPS.(KPWD SR 2018-19, P.No:XLIII, Sl.No.:17)								
	Stand by 1 Nos		2				2		
						Nos	2	22237.2	44474.40
	Basic Rate		20590						
	Area Weightage 8%		1647.2						
	Total		22237.2						
58	Electrification & Automatic On/Off Sensor system	Nos					2		
						Nos	2	25000.00	50000.00
Sub-Total (Civil)									10963272.71
Sub-Total (Electrical)									6866747.40
12% GST									1315592.73
DPR & PMC charges 2%									356400.40
Unforceen									7987.24
Grand Total									19500000.00

[Signature]
Asst. Engineer

[Signature]
Executive Engineer
Yelahanka Zone
Bangalore Mahanagara Palike
Project Division
Yelahanka Zone
BBMP, Bangalore-92

[Signature]
Asst. Exe.Engineer
Sub-Division No.
Bhuvan Bangalore Mahanagara Palike
Asst. Executive Engineer
Project Division
Yelahanka Zone
Bangalore



Technical Sanction
Accorded For *RS 19.50 Lakhs only*
Head of A/C. *P.3590*
CER NO : *85* Dt: *20.09.2019*

Approved by Major Works Committee
vide subject NO: 32/2019-20
Dt 07/02/2020

Administrative Approval

Accorded For *RS. 19.50 Lakhs only*
Head of A/C. *P.3590*
CER NO : *40* Dt: *18/02/2020*

[Signature]
E.E. (Project) *18/2*